



**FROSTED**  
Two-Way 24/7 Privacy



**Description**

A frosted non-perforated window film which blocks see-through, providing privacy on both sides of the window. It allows daylight into rooms and has a unique embossed texture which makes it more appealing than run of the mill frosted films.

 Color  
**Frosted white/gray**

Surface type  
**Textured, non-perforated**

 Installation  
**Inside or Outside Window**

Privacy characteristics  
**DAY: Total privacy**  
**NIGHT: Total privacy**  
**VIEW OUT: Blocked**

 On window durability  
**1 Year**

 Storage (72°F, 55% humidity)  
**1 Year**

**Roll Sizes Available**  
98ft (length) x 48Inch (width)

**Technical Specification**

Face film	<b>Embossed etch PVC, translucent gray</b>
Thickness	<b>6.0 mil +/- 0.4 mil</b>
Transparency	<b>N/A</b>
Adhesive	<b>Clear adhesive</b>
Protective release liner	<b>4.1 oz/yard2(+/-0.3) white PEK paper with silicon coating</b>
Min appl temp	<b>50°F</b>

**Installation Recommendations**

For vertical installation on standard glass. Apply using a wet application method. Glass must be thoroughly cleaned beforehand with soap and water. Rinse and dry glass after cleaning. Not to be applied to fresh paint or ink, polycarbonate, rubber, plastic moldings and certain PVCs. In case of doubt, please test prior to final application. This product is not recommended for use around a sharp angle where there is a limited area either side of the angle. The film must not touch the rubber window molding. Not to be washed within 24 hours of application.

\* Not recommended for use on glass with coatings such as anti-reflective, self-cleaning and scratch-resistance

**Maintenance care**

Wash with soapy water. Gently wipe with lint cloth or soft bristled brush to remove grease and dirt. Take particular care not to damage the edges and corners. Wash off suds and leave to dry.

**Solar Properties**

Data calculated based on film applied to clear glass 0.12" thick.

Visible light transmission	<b>78%</b>
Visible light reflection, exterior	<b>10%</b>
Visible light reflection, interior	
UV transmission	<b>&lt;1%</b>
Solar energy transmission	<b>74%</b>
Solar energy reflection	<b>9%</b>
Solar energy absorption (total)	<b>18%</b>
Glare reduction (relative %)	
g value	<b>0.79</b>
Shading coefficient (SC)	

**Contact Information**

Contra Vision North America, Inc.  
3330 Cumberland Blvd, Suite 500  
Atlanta  
Unites States  
Tel. +1 770 993 6262  
Email: [usasales@contravision.com](mailto:usasales@contravision.com)  
Web: [www.contravision.com](http://www.contravision.com)

This document is intended as a source of information, is given without guarantee, and does not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of the product for their specific intended purpose.