



**HD TRANSLUCENT WHITE**  
24/7 Obscured Vision



**Description**

Micro perforated privacy window film which appears translucent white from both sides. It provides good one-way vision privacy during daytime and helps to obscure the view into buildings at night (with the right internal lighting - see main image).

 Color  
**Translucent White**

 Surface type  
**Micro Perforated**

 Installation  
**Inside or Outside Window**

 Privacy characteristics  
**DAY: Excellent (\*)**  
**NIGHT: Some Privacy**  
**VIEW OUT: Good (milky)**

 On window durability  
**3 Years+**

 Storage (72°F, 55% humidity)  
**2 Years**

 Environmental standard  
**REACH compliant**

**Technical Specification**

Face film	<b>Translucent white polymeric PVC</b>
Thickness	<b>6.0 mil +/- 0.4 mil</b>
Hole pattern	<b>40% micro perforated; 0.04" diameter holes</b>
Adhesive	<b>Transparent, semi-permanent</b>
Protective release liner	<b>Silicone coated paper</b>
Min appl temp	<b>39°F.</b>

**Installation Recommendations**

For vertical installation on standard glass. Apply using a dry application method. Glass must be thoroughly cleaned beforehand with soap and water. Rinse and dry glass after cleaning. Not to be applied to fresh paint or ink, polycarbonate, rubber, plastic moldings and certain PVCs. In case of doubt, please test prior to final application. This product is not recommended for use around a sharp angle where there is a limited area either side of the angle. The film must not touch the rubber window molding. Not to be washed within 24 hours of application.

\* Not recommended for use on glass with coatings such as anti-reflective, self-cleaning and scratch-resistance

**Maintenance care**

Wash with soapy water. Gently wipe with lint cloth or soft bristled brush to remove grease and dirt. Take particular care not to damage the edges and corners. Wash off suds and leave to dry.

**Solar Properties**

Data calculated based on film applied to clear glass 0.12" thick.

Visible light transmission	<b>47%</b>
Visible light reflection, exterior	<b>32%</b>
Visible light reflection, interior	<b>29%</b>
UV transmission	<b>28%</b>
Solar energy transmission	<b>46%</b>
Solar energy reflection	<b>27%</b>
Solar energy absorption (total)	<b>28%</b>
Glare reduction (relative %)	<b>60%</b>
g value	<b>0.54</b>
Shading coefficient (SC)	<b>0.62</b>

**Contact Information**

Contra Vision North America, Inc.  
3330 Cumberland Blvd, Suite 500  
Atlanta  
Unites States  
Tel. +1 888 646 5939  
Email: [usasales@contravision.com](mailto:usasales@contravision.com)  
Web: [www.contravision.com](http://www.contravision.com)

This document is intended as a source of information, is given without guarantee, and does not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of the product for their specific intended purpose.

**Roll Sizes Available**

33ft (length) x 54Inch (width)  
98ft (length) x 54Inch (width)

(\*) A low level of privacy will be given if there is more light on the inside than on the outside of the window, e.g. if the inside is illuminated at night.